

FSD Planning Meeting

2024 Updates and 2025 Objectives

**M.Jakubowski (TFL), A.Alonso(DTFL), I.Calvo (DTFL),
J.Haese(PSO)**



This work has been carried out within the framework of the EUROfusion Consortium, funded by the European Union via the Euratom Research and Training Programme (Grant Agreement No 101052200 — EUROfusion). Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Commission. Neither the European Union nor the European Commission can be held responsible for them.





EUROfusion Facilities Review


- W7-X results have already confirmed the role of the stellarator as a **serious alternative for the reactor core of a future fusion power plant.**
- W7-X provides a springboard towards the development of a next step stellarator:
 - TJ-II: diagnostic & code validation
- **W7-X is an indispensable facility** for the further development of the stellarator concept towards a fusion power plant.
- W7-X also has the potential to support technology development for burning plasma facilities based on long-pulse tokamaks
 - URAGAN-2M: Plasma start-up, wall conditioning
 - FULGOR (KIT): development of heating systems

Recommendation: *EUROfusion should actively promote the timely launching of design and construction of a next step stellarator, leveraging where possible collaboration with international partners, with the goal of providing the scientific/technical basis for a stellarator DEMO.*



Status of Wendelstein 7-X

- Technical commissioning on (revised) schedule:
 - Vacuum conditions of plasma vessel and cryostat ready for operation.
 - Cool-down of SC coils finished
 - Major components (pellet injector, ICRH antenna, NBI/ECH extensions) on track.
 - 2 transformers for NPC-1 coils will be delivered end of June.
- Plasma commissioning starts 3 Sep 2024, shortened to three weeks
- Plasma scientific operation OP2.2 – 24 Sep 2024 until 12 Dec 2024
- Plasma scientific operation OP2.3 – 17 Feb 2025 until 21 May 2025
- Program Workshop took place on 24-24 Apr 2024
- Call for participation issued on June 1st 2024






Enhancements to heating systems

- NBI 55 kV **H injection** with all 4 sources S3, S4, S7, S8
 - injected power approx. 2-2.2 MW
 - pulse length: max. 5 sec integral
- NBI 42 kV **⁴He injection** with 4 sources S3, S4, S7, S8
 - injected power approx. 1.2 MW (tbc)
 - pulse length 5 sec (tbc)
- ICRH (with FZJ, ERM/KMS)
 - Power > 800 kW
 - pulse length up to 10 s
 - Scenarios:
 - H minority in He plasmas
 - ³He minority heating in ⁴He or H
 - 3-ion-heating with ³He, H, ⁴He
 - **Plasma start-up (also at 1.7 T)**
 - **ICRF wall conditioning**



NI20 sources





NI21 sources






ECRH upgrades

- repaired prototype 1.5MW gyrotron under commissioning
- good progress in gyrotron conditioning
- ⇒ Gaussian beam shape demonstrated and centered to diamond window
- ⇒ 1ms pulse length at 1.5MW demonstrated
- ⇒ acceptance tests ongoing (1.5 s of 1MW)
- ⇒ afterwards, tailoring of operation to 1.5MW steady-state







Steady-state pellet injector goes into operation OP2.2



pellet material	H ₂ or D ₂
pellet size	2mm – 3mm (adjustable)
pellet speed	250 – 1000 m/s
repetition frequency	single on demand, continuous up to 10 Hz
injection duration	up to 30min tested
injection modes	feed-forward, density feedback control foreseen beyond OP 2.3





Statistics of proposals for OP2.2 & OP2.3

- We continue operating W7-X in one team approach
- 371 WP W7X related proposals submitted for OP2.2 & OP2.3 (of which 115 prio-1 proposals)
- 15 proposals from WP PWIE (4 prio-1)
- Three task forces:
 - Core Scenario Development
 - Edge Scenario Development
 - W7-X Optimization



Deliverables and milestones 2024/2025

EUROfusion Grant Agreement Deliverables:

- W7X.D.07: Report on the modelling of plasma heating schemes, plasmas with **fast-ions and transport regimes for long steady-state high-beta operation (energy limit 2 GJ)**
- W7X.D.08: Report on conducted Scenario & campaign preparation OP 2.3 (focus: **turbulent and neoclassical transport, high-power steady-state operation**)
- W7X.D.09: Assessment report on scenarios with **optimized transport and high-beta operation** (~~energy limit 6 GJ~~)

Grant Agreement Milestones:

- W7X.M.04: **High-beta HELIAS operation at low collisionalities** achieved
- W7X.M.05: Operation with **high-power and long-pulse** completed and ~~6 GJ energy turn-around~~ achieved (pulse lengths up to 600 s, **long-pulse detachment**)

Research topics for experimental campaigns 2024/2025

ID	Tag	Description
RT-01	High performance conditions	Exploration of reduced turbulence/ high-performance scenarios in view of stationary plasma conditions with temperature-, density and impurity-profile control.
RT-02	Heating scenarios	Exploration of heating scenarios using upgraded heating capabilities (ECRH, NBI, ICRH).
RT-03	High beta scenario development	Development of high plasma beta scenario by low field operation.
RT-04	Long-pulse operation and wall conditioning	Development of integrated scenarios for long-pulse operation with PFC heat-load control, efficient particle exhaust and impurity screening; Development of wall conditioning procedures.
RT-05	Detachment	Development of long and stationary divertor detachment scenarios with and without impurity seeding.

Research topics for experimental campaigns 2024/2025


ID	Tag	Description
RT-06	Tungsten PFCs	Exploration of scenarios compatible with carbon free operation and tungsten PFCs.
RT-07	Documentation of physics basis	Physics basis (core, edge) and reference discharges.
RT-08	Core physics studies	Completion of the core transport and stability physics basis in the extended operational space.
RT-09	Edge physics studies	Completion of the edge and SOL physics basis in the magnetic configuration space of W7-X.



Importance of developing low-B scenarios at W7-X



The development of low-B scenarios at W7-X (namely, 1.7 T for X3-ECH heating) is programatically important because:

- 1. Plasma start-up not based on X2-ECH will be required in a reactor.** At W7-X, the combination of ICH and NBI is being pursued.
- 2. Low-B operation at W7-X allows an easier access to high- β , low- ν^* operation,** potentially close to reactor design values (see next slide).
- 3. Investigate B transport dependencies for reactor projections.** Notably, there is no stellarator scaling of the SOL e-folding length.





Low-B operation allows an easier access to high- β , low- ν^* operation




*Both extrapolations based on best observed W7-X performance



Development of long pulse


- In OP2.2/2.3 the next milestone of LPO will be reached
 - 2 GJ attached discharge (also FIS based on IR cameras will be taken into operation).
- 2 GJ detached, if feedback on plasma radiation will be implemented.
- Additionally scenarios with high performance plasmas will be developed to prolong their duration, e.g. with steady-state pellet injector/NBI.






Development of long pulse operation

Injected energy in the plasma




IAE-CICLOP database, X. Litaudon, et al., Nucl. Fus. (2024)





Reaching goals of W7-X within FP9





Gyrotron development (with KIT, NCSRD, PoliTo)

- Experimental verification of improved cavity cooling.
- Activities to support the manufacturing and testing of the 1.5 MW gyrotron, e.g. Modelling of the magnetic field configuration and the propagation of the electron beam
- Test with short pulse gyrotron of improved gyrotron components in support of 1.5 MW and 2 MW gyrotron
- Simulations of gyrotrons: Perform preliminary component design for the 2 MW gyrotron and studies on the optimization for improving further the 1.5 MW
- Optimization of the resonator - Thermal-hydraulic and thermo-mechanical analysis in support of the optimization of the resonator for improving further the gyrotron performance



W divertor: geometry development

- power exhaust analysis using simple criteria:
 - keep maximum heat load below 10 MW/m² with a heating power of at least 10 MW,
 - keep the heat load only on the divertor targets (> 95%).
 - minimize divertor target surface
- evaluate modified geometries against particle removal requirements: ensure high neutral gas pressure
- identify potential impurity retention drawbacks
 - maximize distance to LCFS
 - keep ionization front away from LCFS


- assessment is naturally based on modeling:

- fast: SMoLID (Simple Model for Loads in Island Divertor)
Catia + EMC3-Lite (checking >200 configurations of standard,

different beta & I_{tor})
final check: EMC3/Eirene

- fast: in development
final check: EMC3/Eirene
DIVGAS

- final check: EMC3/Eirene
ERO2.0




Example: heat loads in the standard configuration moving the outboard baffle inward max. 8 cm to “close” the divertor when there are no loads in the current setup.

Conceptual desing review → end of 2025



MATEO (FZJ)


- Total duration for manipulator and observation system: 1/24 – 12/27
- *Manipulator*
 - Done: CDR, prototype test, final detailed design
 - Next: DDR, order material and components, assemble, test, ship to IPP, install (spring 2026 according to W7-X schedule), commission
- *Observation*
 - In work: optical concept design running, prototype test for first mirror tilting running
 - Next: design up to commissioning as above to be planned according to resources available






TSVV#12 : highlights and plans for 2025

- Quasi-isodynamic stellarators with few field periods, good fast-ion confinement, low bootstrap current and also with reduced turbulent transport. Goodman et al. PRX-Energy 2024
- Piecewise-omnigeneous fields: Finding explanation for good confinement outside the standard pictures. Velasco et al 2024



- MONKES: a fast (< minute/point) and accurate NC kinetic equilibrium solver for the evaluation of the bootstrap current. Escoto, et al., NF (2023)
- Inventing fast metrics for alpha particle losses. Albert et al JPP (2023)
- Global fluid turbulence simulations have been performed in the edge and scrape-off-layer of stellarators using the BOUT++ framework. Shanahan et al. JPP 2024
- Semi-automated divertor plate design algorithm for lower heat loads. Davies et al. (2024)
- A new compact quasi-axisymmetric stellarator-tokamak hybrid concept.



Henneberg, Plunk, PRR (2024)
Schuett, Henneberg (2024)


- Divertor optimisation (to aid development of W divertor at W7-X).
- Free-boundary version of GVEC.
- Comparison of stellarators of different topological classes.

2025




TSVV#13 : highlights and plans for 2025


- The effect of impurities on turbulence has comprehensively been characterized for W7-X and other config. (LHD and ITER).
- Under certain conditions and Z_{eff} a minimum ion heat flux is found [García-Regaña in progress'24].



- Electromagnetic simulations show strong increase of turbulent heat losses at moderate β , attributed to linearly subdominant KBMs [Mulholland PRL'23]



- The TSVV13 has supported the first detection of Zonal Flow (ZF) activity in W7-X with stella and EUTERPE simulations [Carralero in progress'24].



2025

- Support OP2.2 and OP2.3 W7-X campaigns, with emphasis on validation of particle transport of both main and impurity ions, ZFs, electromagnetic effects.
- Immersion in the study of turbulence in 3D-perturbed tokamaks.



Stellarator Database – implementation of the HELIAS physics basis (Mission 8)


- Physics basis for next-step devices
- Documentation of W7-X discharges
- International collaboration to involve other devices
- Objectives
 - Scaling of energy confinement
 - Effect of magnetic configuration on transport
 - Validation of transport models (TSVV)
 - Operation limits
 - Documentation of long-pulse operation (IEA collab.)
 - 3D PWI
 - ...
- Technical implementation to be pursued
- Integration with tokamak databanks

Responsible:

Alfonso Baciero Adrados <alfonso.baciero@ciemat.es>

Tech. support Gloria FALCHETTO <Gloria.FALCHETTO@cea.fr>

EUROfusion building blocks
for the development
of a stellarator fusion reactor





Interface with other WPs

- FTD - WPPRD implements HELIAS engineering activities
 - Support by HELIAS physics basis and experiments on W7-X
- FTD – WPHCD, WPDIV
 - Reliable high-power gyrotrons
 - W7-X metal divertor design – incl. DIVGAS calculations.
- FSD - WPTE, JT60SA, PWIE: fostering European leadership in fields of key expertise
 - metallic wall and 3D modelling
 - safe steady-state operation: surveillance and fast control (also with machine learning)
 - steady-state technology: hardening
 - fast-ions: physics and diagnostics
- International Collaborations
 - ITPA and ITER IO: specific scientific (e.g. EMC3-EIRENE) and diagnostics/technological support (e.g. LaB6 pressure gauges, stray-radiation tests, Thomson Scattering)
 - IEA TCP-SH: participation in the LHD and Heliotron-J experiments
 - DoE laboratories: collaboration on diagnostics and theory




Summary

- Wendelstein 7-X is on the path to provide input for the decision on the next step stellarator and the stellarator-based reactor design
- In 2025 the main focus of the research will be experimental campaigns OP2.2 & 2.3:
 - 2 GJ long pulse detached / attached
 - Operation at lower field → high beta / low collisionality plasmas
 - High performance operation at $T_i = 3$ keV
 - Transition to tungsten PFCs
 - Diagnostics: XICS, dual Thomson scattering, PHA,....
- In the next years, the development and deployment of enhancements will expand the operational space and diagnostic capabilities of the device.
 - Clear objective: approach relevant conditions and clear the way for the *helias* reactor concept..
- Important components like steady-state pellet injector, high power gyrotrons and MATEO in development.




W7-X timeline FP9 and beyond



- planning foresees one operation campaign per year
- due to the time-consuming device commissioning, we will conduct two operation campaigns w/o venting in between, respectively (the cryo system remains cold)
- ⇒ high reliability of systems required (vacuum and cryo systems need to be in full operation for ~1 year)
- ⇒ more efficient use of device for plasma operation




W7-X timeline FP9 and beyond





W divertor: accompanying experimental program

- focus on two main aspects:

1. definition of operation limits (erosion/accumulation) and studies of scrape-off layer retention




observation via divertor spectroscopy



- observation of W eroded from baffle and wall tiles
- injection of W (core or edge) to assess transport of high-Z material in different transport scenarios




Record heating energy of 1.3GJ w/ attached divertor





Upgrades to heating systems



Scenario	Total power	comment
ECRH only, $t < 15s$	8.5MW	All gyrotrons at max. power
ECRH only, long pulse	7.5MW	B1 not available, reduced power of gyrotrons to increase reliability
ECRH + NBI, $t < 15s$	7-8MW	Max. power of gyrotrons in parallel operation to be determined
Stabilized total power	$0.8 * P_{max}$	Individual gyrotron power of 10-11 gyrotrons reduced to compensate failure of 2-3 other gyrotrons

Scenario development with increased confinement and high- β

- stabilization and prolongation of pellet-induced peaked density profile
- improved confinement NBI-ECRH scenario
- high-density ECRH scenario and studies of particle transport
- role of magnetic topology on profile evolution
- direct ion heating via NBI and ICRH
- high- β scenario development at reduced magnetic field: startup and X3 heating

